

**LANDA**<sup>®</sup>  
PRESSURE WASHERS

Since 1969

North America's **LARGEST** Manufacturer  
of Industrial **PRESSURE WASHERS**

# HS

*Oil-Heated, Hot Water Generator That  
Attaches to a Cold Water Pressure Washer*

- Up to 3000 PSI
- Up to 150° F Temperature Rise
- Sch. 80 Heating Coil
- 120V, 1 ph, 5 amps
- Tubed Pneumatic Tires

## HOW IT IS USED

The HS-3000 is an electric-powered, diesel/oil-heated hot water generator that attaches to a cold-water pressure washer essentially turning it into a hot water pressure washer.

The HS-3000 does not have a pump but simply heats the pressurized water—as much as 150°F above the water's ambient temperature, depending on the flow rate—so it can be used for cleaning the toughest of cleaning challenges.

Even though it is more like an accessory, the HS-3000 is packed with all of the quality components that have established the built-to-last reputation for LANDA equipment, including Schedule 80 heating coil, tubed pneumatic tires, and high-efficiency burner.



■ **Extra-durable Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.

■ **Rust-free, 11-gallon Fuel Tank** with elevated fuel line to prevent dirt and debris from reaching burner.

■ **Helpful Tri-Lingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.

■ **9 feet of wire-braid, Hose** with coupler for connecting to cold water pressure washer.

■ **Triple Safety Protection**, including a rupture disk, high-limit thermostat and flow switch to prevent the build up of excessive pressures or heat.

■ **High-efficiency Burner** is easy to access and is protected by coil wrap hood.

■ **36 feet of high-grade Electrical Cord** with **Ground Fault Circuit Interrupter** for operator safety.

■ **Two-ply, tubed Pneumatic Tires** make for easy maneuvering in any terrain.

■ **Rugged 12-gauge steel Chassis** protected by weather-resistant epoxy powder coat paint.



## HS-3000 Specifications

Feature	HS-3000
GPM	Up to 6
PSI	Up to 3000
Temperature Rise*	Up to 150° F
Fuel Tank Capacity	11 Gallons
Electrical	120V, 1 ph, 5 amps
BTU Per Hour	420,000
Dimensions LxWxH	48" x 30" x 35"
Ship Weight	390 lbs.

\* Variable depending on flow rate (3-6 GPM)

## OPTIONS:

Part No.	Description
30-512	Stainless steel outer coil wrap

[www.landa.com](http://www.landa.com)

**LANDA**<sup>®</sup>  
PRESSURE WASHERS

Since 1969

North America's **LARGEST** Manufacturer  
of Industrial **PRESSURE WASHERS**

# NG

*Natural Gas-Heated, Hot Water Generator  
That Attaches to a Cold Water Pressure Washer*

- Up to 3000 PSI
- Up to 150° F Temperature Rise
- Sch. 80 Heating Coil
- LP Conversion Option
- Rugged Steel Frame



## Why Choose the NG Hot Water Generator

The NG-3000 is a stationary, natural gas-heated hot water generator that can be attached to a cold-water pressure washer making it a hot water washer.

The NG-3000 does not have a pump but simply heats the pressurized water—as much as 150°F above the water's ambient temperature, depending on the flow rate—so it can be used for cleaning the toughest of cleaning challenges.

There are two models, a 3000 and 3000 LM—the “LM” version being much larger with a modulating gas valve, able to heat water at flow rates of up to 10.6 GPM. Both models can be converted to LP gas.

The NG models are packed with *LANDA* quality throughout, including Schedule 80 heating coil, high-efficiency burner, rugged steel frame and a raised platform for easy positioning in a shop.

- **Extra-durable Heating Coil** made of leak-free, cold-rolled, Schedule 80 steel pipe with five-year warranty.
- **Helpful Tri-Lingual Labels** with operating instructions in English, Spanish and French for owner and operator protection.
- **9 feet of wire-braid, Hose** with coupler for connecting to cold water pressure washer.

## NG-3000 and NG-3000LM Specifications

Feature	NG-3000	NG-3000LM
GPM	Up to 6	Up to 10.6
PSI	Up to 3000	Up to 3000
Temperature Rise*	Up to 150° F	Up to 150°F
Heating Coil	1/2" Sch 80 / 154 ft.	3/4" Sch 80 / 360 ft.
Inlet Hose	3/8" I.D. x 9 ft.	1/2" I.D. x 9 ft.
BTU Per Hour	420,000	750,000
Dimensions LxWxH	31" x 30" x 48"	38" x 45" x 57"
Ship Weight	450 lbs.	900 lbs.

\* Variable depending on flow rate (3-10 GPM)

## OPTIONS:

Part No.	Description
7-7SVLPKIT	Kit to convert fuel to LP gas for NG-3000 model
7-7VLPKIT	Kit to convert fuel to LP gas for NG-3000LM model

■ **Triple Safety Protection**, including a rupture disk, high-limit thermostat and flow switch to prevent the build up of excessive pressures or heat.

■ **Rugged 12-gauge steel Chassis** protected by weather-resistant epoxy powder coat paint.

■ **High-efficiency Burner** with millivolt ignition and standing pilot; also Robert Shaw gas valve

**LANDA**<sup>®</sup>  
PRESSURE WASHERS

Distributed by:

[www.landa.com](http://www.landa.com)