

**LANDA**<sup>®</sup>  
PRESSURE WASHERS

Since 1969

North America's **LARGEST** Manufacturer  
of Industrial **PRESSURE WASHERS**

# SEA

Stationary, Electric-Powered,  
Cold Water Pressure Washer

- Up to 4.2 GPM, 3000 PSI
- Belt-Drive LANDA Pump with 7-Year Warranty
- Stainless Steel Cabinet
- Time-Delay Shutdown
- Accepts Hot Water Up to 175°F

■ Industrial-grade **Motor** is connected to the rugged, tri-plunger, oil-bath **LANDA High-Pressure Pump** (with 7-year warranty) by dual, heat-dissipating V-cogged belts. **Pulleys** are made of cast iron and can be easily adjusted by turning two bolts.

■ Add portability to the SEA with optional stainless steel **Wheel Kit** (#4-03177), including detergent jug holder. Optional **Hose Reel** (#4-02755030) provides tangle-free handling of up to 100 feet of high-pressure hose.

■ Four quick-couple **Nozzles** are made of hardened stainless steel and color-coded for easy selection of spray pattern: 0°, 15°, 25°, 40°.

■ **Time-Delay Shutdown** automatically turns off unit, if not in use for a set time, for protection against unattended operation.

■ **Inlet Filter** strainer protects pump from debris.

■ 50 ft. of double steel-wire braid **High Pressure Hose** rated for up to 5800 PSI and with 24-inch **Hose Guard** for burst protection and swivel **Crimp Fitting** for tangle-free handling of hose and trigger gun

■ Corrosion-proof **JIC Fittings** are used throughout for ease in servicing and longer life.

■ With the switch in the 'ON' position, the optional **Auto Start** function allows the unit to be turned on with the pull of the trigger for convenient remote operation.

■ Heavy-duty **Cabinet** is made of stainless steel, including base plate, and rides on four **Rubber Feet** for absorption of vibration. The cover can be removed quickly by hand unscrewing four **Star Knobs**.

■ 36 ft. of high-grade **Electrical Cord** with ground fault circuit interrupter (on single-phase models) for operator safety.

■ Helpful **Tri-Lingual Labels** with operating instructions in English, Spanish and French for added liability protection and operator convenience.

■ Insulated, fatigue-free, spring-loaded, 5000 psi **Trigger Gun** with stainless steel, dual-lance **Variable Pressure Wand** make for easy cleaning and adjusting the pressure while washing.



■ Many **Safety Features**, including a thermal pump protector to prevent the build up of excessive pressures or heat.

■ Optional rust-free **Float Tank** with stainless steel inlet filter and backflow protection.

■ Easy-to-attach **detergent Injector** for easy application of soap

[www.landa.com](http://www.landa.com)



Since 1969

North America's **LARGEST** Manufacturer of Industrial **PRESSURE WASHERS**

# SEA

Stationary, Electric-Powered, Cold Water Pressure Washer

- Up to 4.2 GPM, 3000 PSI
- Belt-Drive LANDA Pump with 7-Year Warranty
- Stainless Steel Cabinet
- Time-Delay Shutdown
- Accepts Hot Water Up to 175°F



## WHY CHOOSE LANDA'S SEA

The SEA is the absolute top-of-the-line stationary, cold water pressure washer on the market today. The 8 models feature *LANDA* belt-drive pumps and are ideal for indoor cleaning applications, from food processing to warehouse cleaning.

**QUALITY:** Only the highest quality components are found in the SEA, including the *LANDA* tri-plunger high-pressure pump with 7-year warranty, stainless steel cabinet riding on four vibration-absorbing feet and stainless steel variable pressure wand for maximum cleaning flexibility. Also, the SEA is assembled in a factory certified to the internationally recognized ISO-9001 quality standards.

**SAFETY:** The SEA also is certified to the rigid UL-1776 safety standards making it very safe to operate thanks to its magnetic contactor switch with thermal overload protection, time-delay shutdown, 24-inch hose guard for burst protection, Ground Fault Circuit Interrupter on all single-phase models, and tri-lingual operating instructions.

### SEA Specifications

Part No.	GPM	PSI	Motor HP	Electrical	Amps	Cord Length	Pump RPM	L x W x H	SHIP WT.
SEA3-11021D*	2.8	1000	2	120V 1 ph	20	36 Feet w/GFCI	850	26" x 20" x 16"	205 lbs.
SEA4-20024A	4.2	2000	6.2	230V 1 ph	28	36 Feet w/GFCI	935	26" x 20" x 16"	280 lbs.
SEA4-20024B	4.2	2000	6.2	230V 3 ph	16	10 Feet	935	26" x 20" x 16"	220 lbs.
SEA4-20024C	4.2	2000	6.2	460V 3 ph	7.2	10 Feet	935	26" x 20" x 16"	220 lbs.
SEA4-20024F**	3.5	2000	5	575V 3 ph	6.5	10 Feet	935	26" x 20" x 16"	220 lbs.
SEA4-30024B	3.5	3000	7.5	230V 3 ph	21.5	10 Feet	800	26" x 20" x 16"	235 lbs.
SEA4-30024C	3.5	3000	7.5	460V 3 ph	10.5	10 Feet	800	26" x 20" x 16"	235 lbs.
SEA4-30024F**	3.5	3000	7.5	575V 3 ph	10	10 Feet	735	26" x 20" x 16"	235 lbs.

\* General tri-plunger pump on SEA3-11021D \*\* Also available are models configured to 208V 1ph or 3ph



Distributed by:

### OPTIONS:

Part No.	Description
4-03177	SEA Stainless Steel Wheel Kit
30-640	Wall Mount Bracket Assembly, Stainless Steel
30-5020	E-Zee Reel Hose Reel, 100 ft. & mounting kit (easily mounts to wall mount bracket or wheel kit)
30-487	Automatic Start/Stop (replaces Time-Delay)
30-415	Remote Switch Option
30-332	Float Tank Option

[www.landa.com](http://www.landa.com)